



VICTORY FIRE & GAS INC.
www.victoryfiregas.com
info@victoryfiregas.com

Michigan Corporate Office
1713 Lewis St
Bay City MI 48706
989.322.0856

Texas
15550 West Hardy
Houston TX 77060
281.405.0175

Illinois
162 N. Brandon Dr.
Glendale Heights IL 60139
312.965.2697

Northern CA
2214 American Ave
Hayward CA 94545
510.861.5311

Pennsylvania
30 Three Tun Rd, Unit C
Malvern PA 19335
267.963.6411

Southern CA
14841 Proctor Ave Unit C
City of Industry CA 91746
626.333.3033

Florida
5182 Le Tourneau Circle
Tampa FL 33610
813.999.4424

Georgia
3968 Shirley Drive
Atlanta GA 30336
770.283.4780

CANADA BC
104-1772 Broadway St.
Port Coquitlam, BC V3C2M8
778-222-6765

CANADA Toronto ON
1104 Fewster Drive Unit 12 & 13
Mississauga ON L4W2V7
416-898-6390

CARBON DIOXIDE

20LB CO2 FIRE EXTINGUISHER

MODEL: CO20LB

STANDARD COMPLIED WITH: DOT.ANSI/UL154



FEATURES:

- Suitable for Class B and C Fires
- Plated Brass Valve with Stainless Steel Handles
- Aluminum Cylinder
- 100% Leak Tested
- Production Under ISO9001 Quality System



Valve	 024314001
Seal	 0714025
Lever	 0202148
Rivet	 0204029 0204021
Carry Handle	 0203125
Valve Body	 020504042
Bracket	 070202004 070100022
Safety Gasket	 022304009
Safety Disc	 0233007
Safety Cap	 0212043
O Ring	 020601126 020601127
Valve Stem Assembly	 0220110
Spring	 020701010
Tube Holder	 020801036
Dip Tube	 080402022
Cylinder	 050101131
Safety Pin	 020901003 020901033
Chain	 0210001
Connector	 0242022
Hose Assembly	 080100047
Hoop Assembly	 070200016

TECHNICAL SPECIFICATION

Model Number	CO20LB
Capacity(lb/kg)	20(9.07)
Cylinder Diameter(in/mm)	8(203)
Height(in/mm)	36.02(915)
Width(in/mm)	12.40(315)
Discharge Time(s)	18
Fire Rating	10-B:C
Extinguisher Weight(lb/kg)	47.97(21.76)
Packing Size(L×W×H)(in/mm)	12.8×8.44×27.17(325×215×690)
Discharge Range(ft/m)	4-8(1.2-2.4)
Operation Temperature(F/C)	-22~120(-30~49)
UL list File Number	EX 27916
Marine Type	/
USCG Approval Number	/

* Transport Classification: Non-Flammable, Non-Toxic Gas.
UN No. 1044 Class 2.2