



**VICTORY FIRE & GAS INC.**  
 www.victoryfiregas.com  
 info@victoryfiregas.com

**Michigan Corporate Office**  
 1713 Lewis St  
 Bay City MI 48706  
 989.322.0856

**Texas**  
 15550 West Hardy  
 Houston TX 77060  
 281.405.0175

**Illinois**  
 162 N.Brandon Dr.  
 Glendale Heights IL 60139  
 312.965.2697

**Northern CA**  
 2214 American Ave  
 Hayward CA 94545  
 510.861.5311

**Pennsylvania**  
 30 Three Tun Rd, Unit C  
 Malvern PA 19335  
 267.963.6411

**Southern CA**  
 14841 Proctor Ave Unit C  
 City of Industry CA 91746  
 626.333.3033

**Florida**  
 5182 Le Tourneau Circle  
 Tampa FL 33610  
 813.999.4424

**Georgia**  
 3968 Shirley Drive  
 Atlanta GA 30336  
 770.283.4780

**CANADA BC**  
 104-1772 Broadway St.  
 Port Coquitlam, BC V3C2M8  
 778-222-6765

**CANADA Toronto ON**  
 1104 Fewster Drive Unit 12 & 13  
 Mississauga ON L4W2V7  
 416-898-6390



# CARBON DIOXIDE

## FEATURES:

- Suitable for Class B and C Fires
- Plated Brass Valve with Stainless Steel Handles
- Aluminum Cylinder
- 100% Leak Tested
- Production Under ISO9001 Quality System



## TECHNICAL SPECIFICATION

Model Number	CO5LB	CO10LB	CO15LB	CO20LB
Capacity(lb/kg)	5(2.27)	10(4.54)	15(6.8)	20(9.07)
Cylinder Diameter(in/mm)	5.24(133)	6.89(175)		8(203)
Height(in/mm)	17.13(435)	29.92(760)	35.82(910)	36.02(915)
Width(in/mm)	8.07(205)	11.42(290)		12.40(315)
Discharge Time(s)	9	10	14	18
Fire Rating	2-B:C	10-B:C		10-B:C
Extinguisher Weight(lb/kg)	13.29(6.03)	26.7(12.11)	36.04(16.35)	47.97(21.76)
Packing Size(L×W×H)(in/mm)	7.67×5.7×17.72(195×145×450)	11.62×7.28×20.08(295×185×510)	11.62×7.28×26.77(295×185×680)	12.8×8.44×27.17(325×215×690)
Discharge Range(ft/m)	4-8(1.2-2.4)	4-8(1.2-2.4)		4-8(1.2-2.4)
Operation Temperature(F/C)	-22~120(-30~49)	-22~120(-30~49)		-22~120(-30~49)
UL list File Number	EX 27916	EX 27916		EX 27916
Marine Type	/	B:C Size I	B:C Size II	/
USCG Approval Number	/	162.028 EX 27916		/

\* Transport Classification: Non-Flammable, Non-Toxic Gas. UN No. 1044 Class 2.2