



**VICTORY FIRE & GAS INC.**  
www.victoryfiregas.com  
info@victoryfiregas.com

**Michigan Corporate Office**  
1713 Lewis St  
Bay City MI 48706  
989.322.0856

**Texas**  
15550 West Hardy  
Houston TX 77060  
281.405.0175

**Illinois**  
162 N.Brandon Dr.  
Glendale Heights IL 60139  
312.965.2697

**Northern CA**  
2214 American Ave  
Hayward CA 94545  
510.861.5311

**Pennsylvania**  
30 Three Tun Rd, Unit C  
Malvern PA 19335  
267.963.6411

**Southern CA**  
14841 Proctor Ave Unit C  
City of Industry CA 91746  
626.333.3033

**Florida**  
5182 Le Tourneau Circle  
Tampa FL 33610  
813.999.4424

**Georgia**  
3968 Shirley Drive  
Atlanta GA 30336  
770.283.4780

**CANADA BC**  
104-1772 Broadway St.  
Port Coquitlam, BC V3C2M8  
778-222-6765

**CANADA Toronto ON**  
1104 Fewster Drive Unit 12 & 13  
Mississauga ON L4W2V7  
416-898-6390

# CARBON DIOXIDE

## 5LB CO2 FIRE EXTINGUISHER

### MODEL: C05LB

























#### STANDARD COMPLIED WITH: DOT.ANSI/UL154



### FEATURES:

- Suitable for Class B and C Fires
- Plated Brass Valve with Stainless Steel Handles
- Aluminum Cylinder
- 100% Leak Tested
- Production Under ISO9001 Quality System



Valve		024314001		
Seal		0714025		
Lever		0202148		
Rivet		0204029		0204021
Carry Handle		0203125		
Valve Body		020504042		
Bracket		070200005		070100015
Safety Gasket		022304009		
Safety Disc		0233007		
Safety Cap		0212043		
O Ring		020601126		020601127
Valve Stem Assembly		0220110		
Spring		020701010		
Tube Holder		020801036		
Dip Tube		080402047		
Cylinder		050100088		
Safety Pin		020901003		020901033
Chain		0210001		
Connector		0242021		
Hose Assembly		080100046		

## TECHNICAL SPECIFICATION

Model Number	C05LB
Capacity(lb/kg)	5(2.27)
Cylinder Diameter(in/mm)	5.24(133)
Height(in/mm)	17.13(435)
Width(in/mm)	8.07(205)
Discharge Time(s)	9
Fire Rating	2-B:C
Extinguisher Weight(lb/kg)	13.29(6.03)
Packing Size(L×W×H)(in/mm)	7.67×5.7×17.72(195×145×450)
Discharge Range(ft/m)	4-8(1.2-2.4)
Operation Temperature(F/C)	-22~120(-30~49)
UL list File Number	EX 27916
Marine Type	/
USCG Approval Number	/

\* Transport Classification: Non-Flammable, Non-Toxic Gas.  
UN No.1044 Class 2.2