



ISO 9001



A Quality & Reliable High Pressure
Cylinder/Valve Manufacturer
www.victoryfiregas.com

DOT CARBON DIOXIDE ALUMINUM CYLINDER



Service Pressure: 1800 psi / 124 bar

Standard: DOT-3AL designed, DOT certification

Material: AA 6061

Threads: B5 & larger supplied with 1.125-12 UNF thread, all others with 750-16 UNF.

Finish: Standard finish is polishing body with gray crown.

Graphics: Logos and labels available upon request.

Cleaning: Commercially cleaned & specialty gas cleaned.

Accessories: B10 or larger with valve & carrying handle, others with valve only, Caps & collars or dip tubes available upon request.

SPECIFICATIONS

TYPE #	WATER CAPACITY		DIAMETER		LENGTH		WEIGHT		CO2		NITROGEN cuft
	lbs	liters	in	mm	in	mm	lbs	kgs	lbs	kgs	
DOT-B1	1.5	0.66	3.21	81.5	8.35	212	1.54	0.70	1.0	0.45	2.9
DOT-B1.5	2.2	1.0	3.21	81.5	11.46	291	1.96	0.89	1.5	0.68	4.3
DOT-B1.8	2.6	1.17	3.21	81.5	12.99	330	2.16	0.98	1.8	0.80	5.1
DOT-B2	3.1	1.4	4.38	111.3	9.57	243	3.20	1.45	2	0.95	6.1
DOT-B2.5	3.7	1.7	4.38	111.3	11.02	280	3.57	1.62	2.5	1.16	7.3
DOT-B5	7.5	3.4	5.25	133.4	14.33	364	6.46	2.93	5	2.31	14.7
DOT-B10	14.8	6.7	6.89	175	16.61	422	13.45	6.10	10	4.56	29.0
DOT-B15	22.0	10	6.89	175	23.23	590	17.28	7.84	15	6.80	43.2
DOT-B20	29.5	13.4	8.00	203.2	23.46	596	24.32	11.03	20	9.11	57.9
DOT-B22	32.4	14.7	8.00	203.2	25.47	647	26.46	12.00	22	10.00	63.5
DOT-B35	51.6	23.4	8.00	203.2	38.15	969	36.75	16.67	35	15.91	101.1

*Custom sizes are also available

Victory Fire & Gas Inc.

1713 Lewis Street, Bay City, MI 48706

Phone: 989.322.0856

E-Mail: info@victoryfiregas.com