VICTORY FIRE & GAS INC.

Michigan Corporate Office
1713 Lewis St
Bay City MI 48706
989.322 0856
Email:info@victorygas.com
Website:www.victorygas.com

Texas
15550West Hardy
Houston TX 77060
281 405 0175
Email:info@victorygas.com
Website:www.victorygas.com

Illinois
162 N.Brandon Dr.
Glendale Heights IL 60139
312 515 7715
Email:info@victorygas.com
Website:www.victorygas.com

Northern CA
2214 American Ave
Hayward CA 94545
510.363.8256
Email:info@victorygas.com
Website:www.victorygas.com

Pennsylvania
30 Three Tun Rd, Unit C
Malvern PA19335
267 963 6411
Email:info@victorygas.com
Website:www.victorygas.com

Southern CA
14841 Proctor Ave Unit C
City of Industry CA 91746
626.333 3033
Email:info@victorygas.com
Website:www.victorygas.com

Florida
5182 Le Tourneau Circle
Tampa FL 33610
813 999 4424
Email:info@victorygas.com
Website:www.victorygas.com

Georgia
3968 Shirley Drive
Atlanta GA 30336
Phone: 470 576 4432
Email:info@victorygas.com
Website:www.victorygas.com

British Colombia
1772 Broadway Street-Unit 104
Port Coquitlam BC Canada V3C 2M8
604 464 2871
Email:info@victorygas.com
Website:www.victorygas.com

Ontario
1104 Fewster Drive Unit 12-13
Mississauga ON L4W2V7
416 688 1393
Email:info@victorygas.com
Website:www.victorygas.com

HEAVY DUTY ABC DRY CHEMICAL

FEATURES:

Suitable for Class A B C Fires
Brass Valve
Stainless Steel Handles
Deep Drawn Steel Cylinder With Phosphate Treatment and Powder Coated
High Performance Multipurpose Dry Chemical Powder
100% Helium Leak Tested
Production Under ISO9001 Quality System

UL LISTED ULC LISTED USCG NAFED

TECHNICAL SPECIFICATION

Model Number	PD2.5LB	PD5LB-H	PD10LB	PD20LB
Capacity(lb/kg)	2.5(1.13)	5(2.27)	10.5(4.76)	20(9.07)
Cylinder Diameter(in/mm)	3.45(85)	4.33(110)	5.51(140)	7.16(182)
Height(in/mm)	14.37(365)	17.32(440)	20.16(512)	23.62(600)
Width(in/mm)	6.102(155)	8.9(226)	9.21(234)	10.63(270)
Discharge Time(s)	9	14	22	23
Fire Rating	1-A:10-B:C	3-A:40-B:C	4-A:60-B:C	6-A:80-B:C
Extinguisher Weight(lb/kg)	5.97(2.71)	10.273(4.66)	18.38(8.34)	33.025(14.98)
Packing Size(L×W×H)(in/mm)	6.30×4.13×14.96(160×105×380)	7.48×5.32×18.11(190×135×460)	7.09×5.91×20.87(180×150×530)	8.27×7.48×24.41(210×190×620)
Working Pressure(psi/bar)	195(13.44)	195(13.44)	195(13.44)	195(13.44)
Operation Temperature(F/C)	-40~120(-40~49)	-40~120(-40~49)	-40~120(-40~49)	-40~120(-40~49)
UL list File Number	EX 26837	EX 26837	EX 26837	EX 26837
Marine Type	B:C Size I	A Size II B:C Size I	A Size II B:C Size II	A Size II B:C Size III
USCG Approval Number	162.028 EX 26837	162.028 EX 26837	162.028 EX 26837	162.028 EX 26837

* Transport Classification: Non-Flammable,Non-Toxic Gas. UN No.1044 Class 2.2