



VICTORY FIRE & GAS INC.
 www.victoryfiregas.com
 info@victoryfiregas.com

Michigan Corporate Office
 1713 Lewis St
 Bay City MI 48706
 989.322.0856

Texas
 1555 West Hardy
 Houston TX 77060
 281.405.0175

Illinois
 162 N.Brandon Dr.
 Glendale Heights IL 60139
 312.965.2697

Northern CA
 2214 American Ave
 Hayward CA 94545
 510.861.5311

Pennsylvania
 30 Three Tun Rd, Unit C
 Malvern PA19335
 267.963.6411

Southern CA
 14841 Proctor Ave Unit C
 City of Industry CA 91746
 626.333.3033

Florida
 5182 Le Tourneau Circle
 Tampa FL 33610
 813.999.4424

Georgia
 3968 Shirley Drive
 Atlanta GA 30336
 770.283.4780

CANADA BC
 104-1772 Broadway St.
 Port Coquitlam, BC V3C2M8
 778-222-6765

CANADA Toronto ON
 1104 Fewster Drive Unit 12 & 13
 Mississauga ON L4W2V7
 416-898-6390



HEAVY DUTY/PREMIUM ABC DRY CHEMICAL

FEATURES:

- Suitable for Class A B C Fires
- Brass Valve
- Stainless Steel Handles
- Stainless Steel Cylinder
- High Performance Multipurpose Dry Chemical Powder
- 100% Helium Leak Tested
- Production Under ISO9001 Quality System



TECHNICAL SPECIFICATION

Model Number	PD2.5LB-S	PD5LB-HS	PD10LB-S	PD20LB-S
Capacity(lb/kg)	2.5(1.13)	5(2.27)	10.5(4.76)	20(9.07)
Cylinder Diameter(in/mm)	3.45(85)	4.33(110)	5.51(140)	7.16(182)
Height(in/mm)	14.17(360)	17.12(435)	19.96(507)	23.22(590)
Width(in/mm)	6.102(155)	8.9(226)	9.21(234)	10.63(270)
Discharge Time(s)	9	14	22	23
Fire Rating	1-A:10-B:C	3-A:40-B:C	4-A:60-B:C	6-A:80-B:C
Extinguisher Weight(lb/kg)	5.36(2.43)	9.79(4.44)	18.94(8.59)	33.58(15.23)
Packing Size(L×W×H)(in/mm)	6.30×4.13×14.76(160×105×375)	7.48×5.32×17.91(190×135×455)	7.09×5.91×20.67(180×150×525)	8.27×7.48×24.01(210×190×610)
Working Pressure(psi/bar)	195(13.44)	195(13.44)	195(13.44)	195(13.44)
Operation Temperature (F/C)	-40~120(-40~49)	-40 ~120 (-40~49)	-40 ~120 (-40~49)	-40 ~120 (-40~49)
UL list File Number	EX 26837	EX 26837	EX 26837	EX 26837
Marine Type	/	/	/	/
USCG Approval Number	/	/	/	/

* Transport Classification: Non-Flammable, Non-Toxic Gas. UN No. 1044 Class 2.2