



VICTORY FIRE & GAS INC.
www.victoryfiregas.com
info@victoryfiregas.com

Michigan Corporate Office
1713 Lewis St
Bay City MI 48706
989.322.0856

Texas
15550 West Hardy
Houston TX 77060
281.405.0175

Illinois
162 N.Brandon Dr.
Glendale Heights IL 60139
312.965.2697

Northern CA
2214 American Ave
Hayward CA 94545
510.861.5311

Pennsylvania
30 Three Tun Rd, Unit C
Malvern PA19335
267.963.6411

Southern CA
14841 Proctor Ave Unit C
City of Industry CA 91746
626.333.3033

Florida
5182 Le Tourneau Circle
Tampa FL 33610
813.999.4424

Georgia
3968 Shirley Drive
Atlanta GA 30336
770.283.4780

CANADA BC
104-1772 Broadway St.
Port Coquitlam, BC V3C2M8
778-222-6765

CANADA Toronto ON
1104 Fewster Drive Unit 12 & 13
Mississauga ON L4W2V7
416-898-6390

ABC DRY CHEMICAL

MODEL: PD20LB-AL

























STANDARD COMPLIED: ANSI/UL299



FEATURES:

- Suitable for Class A B C Fires
- Aluminum Valve
- Stainless Steel Handles
- Deep Drawn Steel Cylinder With Phosphate Treatment and Powder Coated
- High Performance Multipurpose Dry Chemical Powder
- 100% Helium Leak Tested
- Production Under ISO9001 Quality System



Valve	 Aluminum Valve 024313020	
Seal	 0714025	
Lever	 Stainless Steel 0202118	
Rivet	 0204029	 0204057
Safety Pin	 30420050	
Chain	 0210001	
Carry Handle	 Stainless Steel 0203089	
Pressure Gauge	 040324	
Valve Body	 Aluminum 200207044	
O Ring	 020603009	
Valve Stem Assembly	 Aluminum 2004120	
Spring	 020701030	
Tube Holder	 Nickel Plated 020802022	
Dip Tube	 Galvanized Steel 080404011	
Cylinder	 050100047	
Bracket	 070200007	 30170061
Hanging Loop	 Aluminum 30920357	 070100013
Screw	 0715038	
Hose Assembly	 Aluminum Parts 080100050	
Strap	 071118	
Hose Catch	 071008	

TECHNICAL SPECIFICATION

Model Number	PD20LB-AL
Capacity(lb/kg)	20(9.07)
Cylinder Diameter(in/mm)	7.16(182)
Height(in/mm)	23.62(600)
Width(in/mm)	10.63(270)
Discharge Time(s)	23
Fire Rating	6-A:80-B:C
Extinguisher Weight(lb/kg)	32.606(14.79)
Packing Size(L×W×H)(in/mm)	8.27×7.48×24.41 (210×190×620)
Working Pressure(psi/bar)	195(13.44)
Operation Temperature (F/C)	-40 ~120 (-40~49)
UL list File Number	EX26837
Marine Type	A Size II B:C Size III
USCG Approval Number	162.028 EX26837

* Transport Classification: Non-Flammable, Non-Toxic Gas.
UN No. 1044 Class 2.2