



VICTORY FIRE & GAS INC.
www.victoryfiregas.com
info@victoryfiregas.com

Michigan Corporate Office
1713 Lewis St
Bay City MI 48706
989.322.0856

Texas
15550 West Hardy
Houston TX 77060
281.405.0175

Illinois
162 N.Brandon Dr.
Glendale Heights IL 60139
312.965.2697

Northern CA
2214 American Ave
Hayward CA 94545
510.861.5311

Pennsylvania
30 Three Tun Rd, Unit C
Malvern PA 19335
267.963.6411

Southern CA
14841 Proctor Ave Unit C
City of Industry CA 91746
626.333.3033

Florida
5182 Le Tourneau Circle
Tampa FL 33610
813.999.4424

Georgia
3968 Shirley Drive
Atlanta GA 30336
770.283.4780

CANADA BC
104-1772 Broadway St.
Port Coquitlam, BC V3C2M8
778-222-6765

CANADA Toronto ON
1104 Fewster Drive Unit 12 & 13
Mississauga ON L4W2V7
416-898-6390

HEAVY DUTY/PREMIUM/HIGH FLOW

ABC DRY CHEMICAL

MODEL: PD20LBHF-S

























STANDARD COMPLIED: ANSI/UL299



FEATURES:

- Suitable for Class A B C Fires
- High Flow for Fast Knockdown
- Brass Valve
- Stainless Steel Handles
- Stainless Steel Cylinder
- High Performance Multipurpose Dry Chemical Powder
- 100% Helium Leak Tested
- Production Under ISO9001 Quality System



Valve	 024313003		
Seal	 0714025		
Lever	 Stainless Steel 0202118		
Rivet	 0204029	 0204057	
Safety Pin	 30420050		
Chain	 0210001		
Carry Handle	 Stainless Steel 0203089		
Pressure Gauge	 040324		
Valve Body	 Brass 020504020		
O Ring	 020603009		
Valve Stem Assembly	 Electroplate 0220148		
Spring	 020701030		
Tube Holder	 Nickel Plated 020802022		
Dip Tube	 Galvanized Steel 080404011		
Cylinder	 Stainless Steel 050100352		
Bracket	 070200007	 Stainless Steel 070200023	 070100013
Hanging Loop	 Stainless Steel 0715037		
Screw	 0715038		
Hose Assembly	 Brass Parts 30290350		
Strap	 071118		
Hose Catch	 071008		

TECHNICAL SPECIFICATION

Model Number	PD20LBHF-S
Capacity(lb/kg)	20(9.07)
Cylinder Diameter(in/mm)	7.16(182)
Height(in/mm)	23.62(600)
Width(in/mm)	10.63(270)
Discharge Time(s)	15
Fire Rating	3-A:40-B:C
Extinguisher Weight(lb/kg)	33.58(15.23)
Packing Size(L×W×H)(in/mm)	8.27×7.48×24.41(210×190×620)
Working Pressure(psi/bar)	195(13.44)
Operation Temperature(F/C)	-40~120(-40~49)
UL list File Number	EX 26837
Marine Type	/
USCG Approval Number	/

* Transport Classification: Non-Flammable, Non-Toxic Gas.
UN No. 1044 Class 2.2