



VICTORY FIRE & GAS INC.
www.victoryfiregas.com
info@victoryfiregas.com

Michigan Corporate Office
1713 Lewis St
Bay City MI 48706
989.322.0856

Texas
15550 West Hardy
Houston TX 77060
281.405.0175

Illinois
162 N.Brandon Dr.
Glendale Heights IL 60139
312.965.2697

Northern CA
2214 American Ave
Hayward CA.94545
510.861.5311

Pennsylvania
30 Three Tun Rd, Unit C
Malvern PA19335
267.963.6411

Southern CA
14841 Proctor Ave Unit C
City of Industry CA 91746
626.333.3033

Florida
5182 Le Tourneau Circle
Tampa FL 33610
813.999.4424

Georgia
3968 Shirley Drive
Atlanta GA 30336
770.283.4780

CANADA BC
104-1772 Broadway St.
Port Coquitlam, BC V3C2M8
778-222-6765

CANADA Toronto ON
1104 Fewster Drive Unit 12 & 13
Mississauga ON L4W2V7
416-898-6390


























ABC DRY CHEMICAL
MODEL: PD5LB-ALH
STANDARD COMPLIED: ANSI/UL299



FEATURES:

- Suitable for Class A B C Fires
- Aluminum Valve
- Stainless Steel Handles
- Deep Drawn Steel Cylinder With Phosphate Treatment and Powder Coated
- High Performance Multipurpose Dry Chemical Powder
- 100% Helium Leak Tested
- Production Under ISO9001 Quality System



Valve	 Aluminum Valve 024313016			
Seal	 0714025			
Lever	 Stainless Steel 0202117			
Rivet	 0204025	 0204021		
Safety Pin	 30420049			
Chain	 0210001			
Carry Handle	 Stainless Steel 0203088			
Pressure Gauge	 040324			
Valve Body	 Aluminum 0205010009			
O Ring	 020603003			
Valve Stem Assembly	 Aluminum 2004119			
Spring	 020701009			
Tube Holder	 Nickel Plated 020802020			
Dip Tube	 Galvanized Steel 080404009			
Cylinder	 050100045			
Bracket	 070200003	 070200009	 070100028	 070100011
Hanging Loop	 Aluminum 30920357			
Screw	 0715038			
Hose Assembly	 Aluminum Parts 080100048			
Strap	 071117			
Hose Catch	 071007			

TECHNICAL SPECIFICATION

Model Number	PD5LB-ALH
Capacity(lb/kg)	5(2.27)
Cylinder Diameter(in/mm)	4.33(110)
Height(in/mm)	17.32(440)
Width(in/mm)	8.9(226)
Discharge Time(s)	14
Fire Rating	3-A:40-B:C
Extinguisher Weight(lb/kg)	9.943(4.51)
Packing Size(L×W×H)(in/mm)	7.48×5.32×18.11 (190×135×460)
Working Pressure(psi/bar)	195(13.44)
Operation Temperature (F/C)	-40 ~ 120 (-40~49)
UL list File Number	EX26837
Marine Type	A Size II B:C Size I
USCG Approval Number	162.028 EX26837

* Transport Classification: Non-Flammable, Non-Toxic Gas.
UN No. 1044 Class 2.2