



**VICTORY FIRE & GAS INC.**  
www.victoryfiregas.com  
info@victoryfiregas.com

**Michigan Corporate Office**  
1713 Lewis St  
Bay City MI 48706  
989.322.0856

**Texas**  
15550 West Hardy  
Houston TX 77060  
281.405.0175

**Illinois**  
162 N.Brandon Dr.  
Glendale Heights IL 60139  
312.965.2697

**Northern CA**  
2214 American Ave  
Hayward CA 94545  
510.861.5311

**Pennsylvania**  
30 Three Tun Rd, Unit C  
Malvern PA19335  
267.963.6411

**Southern CA**  
14841 Proctor Ave Unit C  
City of Industry CA 91746  
626.333.3033

**Florida**  
5182 Le Tourneau Circle  
Tampa FL 33610  
813.999.4424

**Georgia**  
3968 Shirley Drive  
Atlanta GA 30336  
770.283.4780

**CANADA BC**  
104-1772 Broadway St.  
Port Coquitlam, BC V3C2M8  
778-222-6765

**CANADA Toronto ON**  
1104 Fewster Drive Unit 12 & 13  
Mississauga ON L4W2V7  
416-898-6390


























**HEAVY DUTY  
ABC DRY CHEMICAL  
MODEL: PD5LB-H  
STANDARD COMPLIED: ANSI/UL299**



**FEATURES:**

- Suitable for Class A B C Fires
- Brass Valve
- Stainless Steel Handles
- Deep Drawn Steel Cylinder With Phosphate Treatment and Powder Coated
- High Performance Multipurpose Dry Chemical Powder
- 100% Helium Leak Tested
- Production Under ISO9001 Quality System



Valve				
	024313002			
Seal				
	0714025			
Lever				
	Stainless Steel 0202117			
Rivet				
	0204025	0204021		
Safety Pin				
	30420049			
Chain				
	0210001			
Carry Handle				
	Stainless Steel 0203088			
Pressure Gauge				
	040324			
Valve Body				
	Brass 020504019			
O Ring				
	020603003			
Valve Stem Assembly				
	Electroplate 0220103			
Spring				
	020701009			
Tube Holder				
	Nickel Plated 020802020			
Dip Tube				
	Galvanized Steel 080404009			
Cylinder				
	050100045			
Bracket				
	070200003	070200009	070100028	070100011
Hanging Loop				
	Stainless Steel 0715037			
Screw				
	0715038			
Hose Assembly				
	Brass Parts 080100027			
Strap				
	071117			
Hose Catch				
	071007			

**TECHNICAL SPECIFICATION**

Model Number	PD5LB-H
Capacity(lb/kg)	5(2.27)
Cylinder Diameter(in/mm)	4.33(110)
Height(in/mm)	17.32(440)
Width(in/mm)	8.9(226)
Discharge Time(s)	14
Fire Rating	3-A:40-B:C
Extinguisher Weight(lb/kg)	10.273(4.66)
Packing Size(L×W×H)(in/mm)	7.48×5.32×18.11 (190×135×460)
Working Pressure(psi/bar)	195(13.44)
Operation Temperature ( F/C)	-40 ~120 (-40~49)
UL list File Number	EX26837
Marine Type	A Size II B:C Size I
USCG Approval Number	162.028 EX26837

\* Transport Classification: Non-Flammable, Non-Toxic Gas.  
UN No.1044 Class 2.2