



VICTORY FIRE & GAS INC.
www.victoryfiregas.com
info@victoryfiregas.com

Michigan Corporate Office
1713 Lewis St
Bay City MI 48706
989.322.0856

Texas
15550 West Hardy
Houston TX 77060
281.405.0175

Illinois
162 N. Brandon Dr.
Glendale Heights IL 60139
312.965.2697

Northern CA
2214 American Ave
Hayward CA 94545
510.861.5311

Pennsylvania
30 Three Tun Rd, Unit C
Malvern PA 19335
267.963.6411

Southern CA
14841 Proctor Ave Unit C
City of Industry CA 91746
626.333.3033

Florida
5182 Le Tourneau Circle
Tampa FL 33610
813.999.4424

Georgia
3968 Shirley Drive
Atlanta GA 30336
770.283.4780

CANADA BC
104-1772 Broadway St.
Port Coquitlam, BC V3C2M8
778-222-6765

CANADA Toronto ON
1104 Fewster Drive Unit 12 & 13
Mississauga ON L4W2V7
416-898-6390

WET CHEMICAL

6L WET CHEMICAL FIRE EXTINGUISHER

MODEL: WC6L





STANDARD COMPLIED WITH: ANSI/UL8



FEATURES:

- Suitable for Class A and K Fires
- Plated Brass Valve with Stainless Steel Handles
- Stainless Steel Cylinder
- 100% Helium Leak Tested
- Production Under ISO9001 Quality System



Valve		024313004				
Seal		0714025				
Lever		0202118				
Rivet		0204029		0204057		
Carry Handle		0203089				
Valve Body		020504045				
Bracket		070200007		070200010		070100016
Screw		0715038				
Hanging Loop		0715037				
Hose Assembly		080100093				
Cylinder		0501000244				
Safety Pin		020901003		020901033		
Chain		0210001				
Pressure Gauge		040332				
Valve Stem Assembly		Electroplate 0220148				
O Ring		020603009				
Spring		020701040				
Ring Nut		0234004				
Dip Tube Assembly		080408005				
Anti-overfill Tube		2012029				
Strap		071118				
Hose Catch		071007				

TECHNICAL SPECIFICATION

Model Number	WC6L
Capacity(gal/l)	1.6(6)
Cylinder Diameter(in/mm)	7.07(179.5)
Height(in/mm)	19.30(490)
Width(in/mm)	9.65(245)
Discharge Time(s)	51
Fire Rating	1-A:K
Extinguisher Weight(lb/kg)	21.56(9.78)
Packing Size(L×W×H)(in/mm)	7.48×7.48×19.88(190×190×505)
Working Pressure(psi/bar)	100(6.9)
Discharge Range(ft/m)	10-12(3-3.6)
Operation Temperature(F/C)	40~120(4~49)
UL list File Number	EX 28016
Marine Type	/
USCG Approval Number	/

* Transport Classification: Non-Flammable, Non-Toxic Gas.
UN No. 1044 Class 2.2