



VICTORY FIRE & GAS INC.

www.victoryfiregas.com
info@victoryfiregas.com

Michigan Corporate Office
1713 Lewis St
Bay City MI 48706
989.322.0856

Texas
15550 West Hardy
Houston TX 77060
281.405.0175

Illinois
162 N. Brandon Dr.
Glendale Heights IL 60139
312.965.2697

Northern CA
2214 American Ave
Hayward CA 94545
510.861.5311

Pennsylvania
30 Three Tun Rd, Unit C
Malvern PA 19335
267.963.6411

Southern CA
14841 Proctor Ave Unit C
City of Industry CA 91746
626.333.3033

Florida
5182 Le Tourneau Circle
Tampa FL 33610
813.999.4424

Georgia
3968 Shirley Drive
Atlanta GA 30336
770.283.4780

CANADA BC
104-1772 Broadway St.
Port Coquitlam, BC V3C2M8
778-222-6765

CANADA Toronto ON
1104 Fewster Drive Unit 12 & 13
Mississauga ON L4W2V7
416-898-6390



WET CHEMICAL

FEATURES:

Suitable for Class A and K Fires
Plated Brass Valve with
Stainless Steel Handles
Stainless Steel Cylinder
100% Helium Leak Tested
Production Under ISO9001
Quality System



TECHNICAL SPECIFICATION

Model Number	WC2.5GL	WC6L
Capacity(gal/l)	2.5(9.46)	1.6(6)
Cylinder Diameter(in/mm)	7.07(179.5)	7.07(179.5)
Height(in/mm)	24.80(630)	19.30(490)
Width(in/mm)	9.65(245)	9.65(245)
Discharge Time(s)	101	51
Fire Rating	1-A:K	1-A:K
Extinguisher Weight(lb/kg)	31.75(14.40)	21.56(9.78)
Packing Size(L×W×H)(in/mm)	7.48×7.48×25.39(190×190×645)	7.48×7.48×19.88(190×190×505)
Working Pressure(psi/bar)	100(6.9)	100(6.9)
Discharge Range(ft/m)	10-13(3-4)	10-12(3-3.6)
Operation Temperature(F/C)	40~120(4~49)	40~120(4~49)
UL list File Number	EX 28016	EX 28016
Marine Type	/	/
USCG Approval Number	/	/

* Transport Classification: Non-Flammable, Non-Toxic Gas. UN No. 1044 Class 2.2